

imagePRESS V900 series

COMPACT AND RELIABLE DIGITAL COLOUR PRESS WITH INNOVATIVE TECHNOLOGIES

Robustly built and with sustainability a key consideration, the series has been engineered for continuous, reliable productivity, consistent, stable colour and class-leading front and back registration accuracy



Maximise efficiency

Featuring progressive technology that takes its performance to a new level, the V Series helps you overcome your everyday production challenges

Print in high quality

Ensure consistent print quality across all documents by automatically adjusting colour with the in-line spectrometric sensor.

Expand your application range

Extensive media-handling capabilities mean you can print a wide range of media including envelopes, business cards, thin coated paper, and luxury textured paper.

Optimal space utilisation

Compact design to fit into your environment with A magnetic plate on the edge of the printer also provides space to attach notes.

More automation

Designed to reduce turnaround time and the skills required to produce high-quality output.

Canon

TECHNICAL SPECIFICATIONS

imagePRESS V900 series

MAIN UNIT

PRINT SPECIFICATIONS

Print speed (BW/CL)
Recommended monthly volume
Maximum monthly peak volume
Registration tolerance
Printing method
Print Resolution (dpi)

| imagePRESS V900 | imagePRESS V800 | imagePRESS V700 |
|----------------------------|------------------------|------------------------|
| 90 ppm | 80 ppm | 70 ppm |
| 40,000 - 250,000 pages | 30,000 - 220,000 pages | 15,000 - 190,000 pages |
| Up to 500,000 pages | Up to 400,000 pages | Up to 350,000 pages |
| Front to Back: 0.8 mm | | |
| Colour Laser Beam Printing | | |
| 2,400 x 2,400 | | |

PAPER SUPPLY OPTIONS

Paper supply capacity (A4, 80gsm)

Standard: 1,650 sheets
 550-sheet Paper Cassette x 3
 Maximum: 10,400 sheets
 (Engine (550x3), Multi Drawer Deck(1,500+1,500+2000), POD Deck Lite XL(3,500), Bypass(250))

Supported media types

Engine Drawer :
 Thin(52-63gsm), Plain(64-105gsm), Thick(106-300gsm), Recycled, Color, Tab, Transparency, Bond, Pre-punched, Letterhead, Postcard, Envelope

Multi Drawer Deck-E1

Upper/Middle :
 Thin(52-63gsm), Plain(64-105gsm), Recycled, Color, Thick(106-350gsm), Coated(70-350gsm), Embossed, Bond, Transparency, Label, Pre Punched, Letterhead, Index, Bellum, Transparent film, Translucent film, Envelope*

Lower :
 Thin(52-63gsm), Plain(64-105gsm), Recycled, Color, Thick(106-350gsm), Coated(70-350gsm), Embossed, Bond, Transparency, Label, Pre Punched, Letterhead, Index, Transparent film, Translucent film, Envelope*, Synthetic, Magnetic(TBD)

POD Deck Lite :
 Thin(52-63gsm), Plain(64-105gsm), Recycled, Color, Thick(106-350gsm), Coated(85-350gsm), Embossed, Bellum, Bond, Transparency, Transparent film, Translucent film, Label, Pre Punched, Letterhead, Index, Postcard, Envelope, Synthetic

POD Deck Lite XL :
 19.2" or shorter
 Thin(52-63gsm), Plain(64-105gsm), Recycled, Color, Thick(106-350gsm)*, Coated(85-350gsm)*, Embossed, Bellum, Bond, Transparency, Transparent film, Translucent film, Label, Pre Punched, Letterhead, Index, Postcard, Envelope, Synthetic

Longer than 19.2"
 Uncoated(64-300gsm), Coated(100-300gsm)

Supported media sizes

Multi-purpose tray:
 Thin(52-63gsm), Plain(64-105gsm), Recycled, Thick(106-350gsm), Color, Transparency, Label, Postcard, Envelope, Coated(70-350gsm), Embossed, Bond, Pre-punched, Letterhead, Vellum, Tab

Engine Drawer :
 A3S, B4S, A4L, A4S, B5S, B5L, A5S, A5L, A6S, SRA3S, 11"x17"S, LGLS, LTRL, LTRS, EXE_L, STMTS, 12"x18"S, 13"x19"S, 8KS, 16KL, 16KS, Envelope, Custom size (Cross track:100-330.2mm, In track:148-487.7mm)

Envelope specification
 Size:ISO-C5, DL
 Custom size :
 Cross track: 98-330.2mm,
 In track: 148mm-487.7mm

POD Deck Lite :
 SRA3S, A3S, A4L, A4S, A5S, B4S, B5L, B5S, 13"x19"S, 12"x18"S, 11"x17"S, LGLS, LTRL, LTRS, EXECL, STMS, 8KS, 16KL, 16KS, DL, ISO-C5 *

Custom(139.7x182.0mm-330.2x487.7mm)
 Envelope custom size(6"x9", 9"x12", 10"x13")¹⁾

¹⁾Optional Envelope kit is needed (except10"x13")

POD Deck Lite XL :
 SRA3S, A3S, A4L, A4S, A5S, B4S, B5L, B5S, 13"x19"S, 12"x18"S, 11"x17"S, LGLS, LTRL, LTRS, EXECL, STMS, 8KS, 16KL, 16KS, DL, ISO-C5*
 Custom(139.7x182.0mm-330.2x487.7mm)

* Optional envelop kit is needed

Long Sheet(297.0x487.8-330.2x762.0mm)

Multi Drawer Deck-E1

Universal Cassette:
 SRA3S, A3S, A4L, A4S, A5S, B4S, B5L, B5S, 13"x19"S, 12"x18"S, 11"x17"S, LGLS, LTRL, LTRS, EXECL, STMTS, 8KS, 16KL, 16KSDL, DL, ISO-C5*

Custom(139.7x182.0mm-330.2x487.7mm)
 Custom Envelope(6"x9", 9"x12", 10"x13")¹⁾

¹⁾Optional envelop kit is needed

Supported media weights

Machine type
Core functions
Processor
Control Panel
Memory
Hard Disk drive
Mirroring Hard Disk Drive
Interface Connection
Power <supply
Dimensions main engine (W x D x H)

Multi-purpose tray:
 A3S, B4S, A4L, A4S, B5S, B5L, A5S, A5L, A6S, SRA3S, 11"x17"S, LGLS, LTRL, LTRS, EXECL, STMTS, 12"x18"S, 13"x19"S, 8KS, 16KL, 16KS, Envelope Monarch, DL, ISO-C5

Custom size(Cross track:100-330.2mm, In track:148-487.7mm)
 Long Sheet(210.0x487.8-330.2x1,300.0mm)
 Envelope Custom size:
 (98.0x148.0mm-330.2mmx487.7mm)

Engine Drawer: 52 to 300 gsm
 Multi Drawer Deck: 52 to 350 gsm
 POD Deck Lite: 52 to 350 gsm
 POD Deck Lite XL: 52-350 gsm
 Multi-purpose tray: 52 to 350 gsm

A3 Colour Laser Multifunctional
 Print, Copy, Scan, Send, Store

1.8GHz Dual Core
 10.1 inch WSVGA

6GB
 SSD 512GB
 SSD 512GB

NETWORK
 Standard: 1000Base-T/100Base-TX/10Base-T

220-240V 50/60Hz 13A+13A
 1,327mm* x 872mm x 1,185 mm** (W x D x H)

*Includes optional Control panel and Copy Tray-R2
 ** Includes Operation Panel-A1 Reader-P1 (If Operating Panel-A5 and Operator Attention Light-A1 are attached, total height is 1,632 mm)

Installation Space(W x D) Weight

Approx 284kg

*includes ADF

COPY SPECIFICATIONS

First-Copy-Out Time (A4) (BW/CL)
Copy resolution (dpi)

BW 7.4 seconds or less
 CL 8.2 seconds or less
 600dpix600dpi
 600dpix300dpi
 300dpix300dpi

Multiple Copies
Copy Density
Magnification
Preset Reductions
Preset Enlargements
Basic Copy Features

Up to 9,999 copies
 Automatic or Manual (9 Levels)
 25% - 400% (1% Increments)
 25%, 50%, 70%
 141%, 200%, 400%
 Preset R/E Ratios by Area, Paper Setting, Previous Setting, Favourite Setting, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

Special Copy Features

Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Job Done Notice, Mirror Image, Print on Tab, Store in Mail Box, Superimpose Image, Copy ID Card, Skip Blank Pages, Detect Feeder Multi Sheet Feed, Free Size Original

SCAN SPECIFICATIONS

Name
Type

Duplex Color Image Reader Unit
 Colour Platen and Single-pass Duplexing Automatic Document Feeder* [2-sided to 2-sided (Automatic)]

* Detect Feeder Multi Sheet Feed is supported.

Document Feeder Paper Capacity (80 gsm)
Acceptable originals and weights

200 sheets (75/80gsm)
 Sheet, Book, 3-Dimensional objects

Supported media sizes

Document Feeder media weight:
 <Single sided>
 38-220gsm (A/B)(^(*))(^(*)),
 50-220gsm (inch)(^(*))(^(*))
 <Double sided>
 38-220gsm (A/B)(^(*))(^(*))(^(*)),
 50-220gsm (inch)(^(*))(^(*))(^(*))

(^(*)) 38-50gsm: Thin mode,160-220gsm: heavy mode
 (^(*))A6R or less: 50-220gsm
 (^(*))BW/CL mixed original same as Non mixed
 Platen: max. scanning size: 297.0 x 431.8 mm

Scan Speed (ipm: BW/CL; A4)

Document Feeder media size: A3S, A4L, A4S, A5L, A5S, A6S, B4S, B5L, B5S, B6S, 11"x17"S, LGLS, LTRL, LTRS, STMTL, STMTS, 8KS, 16KL
 BW:270ipm(A4/LTR)(^(*))
 CL:270ipm(A4/LTR)(^(*))
 (^(*))Plain mode



TECHNICAL SPECIFICATIONS

imagePRESS V900 series

| | | | |
|----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Scan Resolution (dpi) | 600dpix600dpi 600dpix300dpi 300dpix300dpi | OUTPUT OPTIONS | |
| CONSUMABLES | | Staple finisher-AG1 | Upper Tray (A) Capacity: A4/A4R/A5R/A3/SRA3/13"x19" 1,000 sheets (52-300 gsm) / 200 sheets (301-350 gsm) Long sheet (Over 487.7 mm up to 762 mm length) 100 sheets (52-79 gsm) / 50 sheets (80-150 gsm) / 25 sheets (151-300 gsm) / 20 sheets (301-350 gsm) |
| Toner Cartridges | TONER T01 BK/C/M/Y | | Lower Tray (B) Capacity: A4 4,000 sheets (52-80 gsm) / 3,000 sheets (801-300 gsm), A4R 2,000 sheets (52-300 gsm), A3 1,500 sheets (52-300 gsm), SRA3 1,000 sheets (52-300 gsm), Any size 200 sheets (301-350 gsm) Paper Weight: 52 to 350 gsm Staple Position: Corner, Double Staple Capacity: A4: 100 sheets, A3/A4R: 50 sheets Dimensions (W x D x H): 800 mm x 792 mm x 1,239 mm (with Long Sheet Tray : 1,136 mm x 792 mm x 1,239 mm) Weight: Approx. 130 kg Power: 220-240V, 50-60Hz, 8A |
| FIERY PRINT CONTROLLER SPECIFICATIONS | | Booklet finisher-AG1 | Tray Capacity / Paper Weight / Staple Position / Staple Capacity: same as Staple Finisher-AG1 Booklet stitch paper size: A3, A4R, SRA3, 13"x19", Free size (210 x 279.4 mm to 330.2 x 487.7 mm) Booklet stitch paper weight: Body sheet 52-220 gsm, Cover sheet 64-300 gsm Booklet stitch staple capacity: 25 sheets (52-80 gsm, include cover) Dimensions (W x D x H): 800 mm x 792 mm x 1,239 mm (with Long Sheet Tray : 1,136 mm x 792 mm x 1,239 mm) Weight: Approx. 180 kg Power: 220-240V, 50-60Hz, 8A Non Staple Folded Bunch Capacity: up to 5 sheets (60 to 105 gsm) Power Source: 100-240V, 50/60Hz, 2.8A Dimensions (W x D x H): 896 x 765 x 1,040 mm (when the extension tray is extended) Weight: Approx. 110 kg |
| Optional/Standard | Optional | | |
| Name | imagePRESS Server N500/P400 | | |
| Print Resolution (dpi) | 1200 x 1200, 600 x 600 | | |
| Page Description Language(s) | PS3/PCL6 | | |
| Memory | 8GB | | |
| Hard Disk Drive | N500: HDD 1TB SSD 240GB P400: HDD 500GB | | |
| Processor Speed | N500: Intel Core i5 8500 P400: Intel Pentium Gold G5400 | | |
| System | N500: FS500 Pro P400: FS500 | | |
| Fonts | PS:138, PCL:80 | | |
| Supported Operating Systems | Windows 8.1 32/64, Windows 10 32/64, Windows 11 64, Windows Server 2012 64, Windows Server 2012 R2 64, Windows Server 2016 64, Windows Server 2019 64, Windows Server 2022 64, macOS Mojave (10.14.x), macOS Catalina (10.15.x), macOS Big Sur(version 11.0), macOS Monterey(version 12) | | |
| Interface | N500: 2 x Ethernet(1000Base-T/100Base-TX/10 Base-T), USB3.2 x 5, USB2.0 x 2 P400: 2 x Ethernet(1000Base-T/100Base-TX/10 Base-T), USB3.0 x 2 | | |
| Network protocols | TCP/IP (FTP, SMTP, POP, HTTP, SNMP, LDAP, SMB, LPD, IPP, WS-Discovery, Bonjour, Direct Mobile Printing, Port 9100, 802.1X, DHCP, DNS, NTP) | Puncher unit-BT1/BU1 | (Requires either the STAPLE FINISHER-AG1 or BOOKLET FINISHER-AG1) Two or Four Holes Punch Hole type: BT1: 2 holes and 4 holes (FRN) selectable, BU1: 4 holes (SWE) Punch Paper Weight: 52-300 gsm Punch Paper Size: 2 holes: A3, A4, A4R, Free size (182 x 182 mm to 297 x 432.0 mm excluding 203 x 257 mm to 297 x 270 mm) 4 holes: A3, A4, Free size (257 x 182 mm to 297 x 432 mm) |
| Direct Print | PDF2, EPS, TIFF, JDF1.8/JMF | | |
| VDP | N500: PPML3.0, PDF/VT-1, PDF/VT2, VPS, FreeForm, FreeForm Plus P400: PDF/VT-1(Requires Fiery JobExpert and PDF Processing Kit), FreeForm, FreeForm Plus | | |
| Fiery Print Controller Standard Features | Fiery Command WorkStation 6 / Paper Catalog / Fiery Remote Scan / Fiery Hot Folders & Virtual Printers | | |
| Fiery Print Controller Options | Fiery Impose / Fiery Compose / Fiery Impose and Compose / Removable HDD Kit(N500 only) | | |
| HW Platform | N500: NX Pro P400: E500 | Copy tray-R2 | Paper Size: All available size on marking engine Paper Weight: 52 to 350 gsm Output Capacity: 250 sheets at simplex/duplex printing, 100 sheets at length over 487.7 mm (Long Sheet Tray is required) Dimensions (W x D x H): 422 mm x 382 mm x 175 mm Weight: Approx. 1.2 kg |
| Dimensions (W x D x H) | tbd | | |
| Weight | tbd | | |
| PRISMA SYNCCONTROLLER SPECIFICATIONS | | Multi function professional puncher-C1 | (Requires either the STAPLE FINISHER-AG1 or BOOKLET FINISHER-AG1) Paper Weight: <Punch> 75-300 gsm (Plain paper), 118-300 gsm (Coated paper) <Crease> 157-300 gsm (Plain paper / Coated paper) <Through> All substrates supported by engine Paper Size: <Through> All substrates supported by engine <Punch> SRA3, A3, SRA4, SRA4R, A4, A4R <Crease> SRA3, A3, A4R, 13"x19", 13"x19.2" |
| Optional/Standard | Optional | | |
| Name | PRISMAsync for iPR V900 series | | |
| Print Resolution (dpi) | 1200x1200dpi, 600x600dpi | | |
| Page Description Language(s) | Postscript L3, PDF 2.0, APPE V5.7, PPML, IPDS (IS/3 standard compliant), PCL/PJL (transaction printing) | | |
| Memory | 1x DDR4-2400 8GB, 8GB total | | |
| Hard Disk Drive | 1x 500GB 2.5 inch, 1x TB 3.5 inch | | |
| Processor Speed | Intel Core i5-8500 (8th Gen Coffee Lake CPU) | | |
| System | PRISMAsync Mark 9 | | |
| Fonts | 139 Type 1 fonts for Roman languages; User import of PS fonts via Settings Editor; Optional Adobe Asian fonts: Japanese: 5 fonts Chinese: 2 fonts for simplified Chinese, 1 font for traditional Chinese; Korean: 1 font for Korean | | |
| Supported Operating Systems | Windows Server 2012 R2, 8.1 (32/64bit) and 10, Server 2016 & 2019 MacOS 10.15 (64 bit), MacOS 11 (64 bit, Big Sur, Intel) | | |
| Interface | Ethernet 10/100/1000 BaseT x 2 USB3.0x8 | Booklet trimmer-F1 | Requires Booklet Finisher-AG1 Trim Width: 2-28mm Trim Thickness: Up to 50 sheets (include cover) Paper Weight: 52 to 300 gsm Chip tray capacity: Approx. 5,000 sheets (Trim width 20mm, A4, 80 gsm) Dimensions (W x D x H): 2,095 mm (including joint, conveyor and output tray) x 790 mm x 1,040 mm Weight: Approx. 178 kg (including conveyor and output tray) |
| Network protocols | TCP/IP, IPv6 Support, IPSec, NetBEUI/SMB (hotfolders, scan-to-file), secure IPP, SNMP V3, Job MIB, HTTP, HTTPS, Socket printing (port9100), LPR/LPD, JDF/JMF, LDAP, WebDav. | | |
| Direct Print | PDF, JDF | | |
| VDP | PDF/VT-1, PPML | | |
| PRISMAsync Controller Standard Features | PS/PDF, Scheduler, Multiple Queues/hotfolders, Streaming, Accounting, Scanning, PPML, Remote Manager, Remote Service, Integrity checker, Windows 10 LTSC | Two-Knife Booklet Trimmer-B1 and Two-Knife Booklet Trimmer Conveyor-B1 | Requires Booklet Trimmer-G1 Trim Width: 2-15 mm Trim Thickness: Up to 50 sheets (include cover) Paper Weight: 52 to 300 gsm (Trim 60 to 300 gsm) Chip tray capacity: Approx. 1,500 sheets (Trim width 15mm, A4, 80 gsm) Dimensions (W x D x H): 2,312 mm (including Booklet Trimmer-F1) x 790 mm x 1,040 mm Weight: Approx. 145 kg Power: 220-240V, 60Hz, 2.3A |
| PRISMAsync Controller Options | E-shredding, Advanced Color Management, Advanced Impose, DocBox, Page Programming, DP Link, PCL6 TP, IPDS, PDF for IPDS | | |
| Dimensions (W x D x H) | 200mm x 430mm x 420mm | | |
| Weight | 18 kg | | |

TECHNICAL SPECIFICATIONS

imagePRESS V900 series

| | | | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>Document insertion unit-r1</p> | <p>(Requires either the STAPLE FINISHER-AG1 or BOOKLET FINISHER-AG1) Number of trays: 2 Tray Capacity: Upper Tray: 200 Sheets (80 gsm), Lower Tray: 200 Sheets (80 gsm) Acceptable Paper Type: Thin, Plain, Recycled, Colour, Thick, Pre-punched, Letterhead, Bond, Coated, Tab, Tracing, Textured Acceptable Paper Sizes: SRA3, A3, A4, A4R, B4, B5, B5R, Custom size (182.0 x 182.0 mm to 330.2 x 487.7 mm) Acceptable Paper Weight: 52 to 300 gsm Power Source: 100-240V/50/60Hz 1.0A Dimensions (W x D x H): 336 x 793 x 1,407 mm (width excluding document tray) Weight: Approx. 61 kg</p> | <p>Booklet Finisher-AC2 (only compatible with V800 and V700)</p> | <p>Tray Capacity / Paper Weight / Staple Position / Staple Capacity: same as Staple Finisher-AC2 but if there are any sheets on the saddle tray, the capacity of Tray A becomes limited to 1,500 sheets Booklet stitch paper size: A3, A4R, Free size (195 x 270 mm to 304.8 x 457.2 mm) Booklet stitch paper weight: Body sheet 52-220 gsm, Cover sheet 52-256 gsm Booklet stitch staple capacity (including 1 cover sheet): Non coated media; 20 sheets (52-81.4 gsm), 10 sheets (82-105 gsm), 5 sheets (106-150 gsm), 4 sheets (151-209 gsm), 3 sheets (210-220 gsm) Coated media; 5 sheets (85-150 gsm), 4 sheets (151-209 gsm), 3 sheets (210-220 gsm) Dimensions (W x D x H): 527 mm (Max 656 mm*) x 623 mm x 1,099 mm (Max 1,195 mm*)</p> |
| <p>Paper folding unit-k1</p> | <p>(Requires either the STAPLE FINISHER-AG1 or BOOKLET FINISHER-AG1) Supported Folding Type: Z-Fold, Accordion Z-Fold, C-Fold, Half-Fold, Double Parallel Fold Acceptable Paper Type: Thin, Plain, Recycled, Colour, Bond Acceptable Paper Sizes: Z-Fold : A3, A4R , B4 Accordion Z-Fold, C-Fold, Half-Fold, Double Parallel Fold: A4R Acceptable Paper Weight: Z-Fold, Accordion Z-Fold, C-Fold, Half-Fold :52 to 105 gsm Double Parallel Fold : 52 to 90 gsm Power Source: From the Finisher Dimensions (W x D x H): 336 x 793 x 1,190 mm Weight: Approx. 71 kg</p> | <p>Booklet Finisher-AC2 (continued)</p> | <p>*when the auxiliary tray is extended. Weight: Approx. 60 kg Requires either Staple or Booklet Finisher-AC1. Paper Weight: Non Sort 52-300 gsm, Bunch Shift 52-256 gsm Paper Size: Non Sort A3/A4/A4R, Bunch Shift A3/A4/A4R 2/4 Hole Puncher Unit-A1 Requires either Staple or Booklet Finisher-AC1. Punch Hole type: 2 holes and 4 holes (FRN) selectable Paper Weight: 52-300 gsm Paper Size: 2 holes: A3, A4, A4R 4 holes: A3, A4 4 Hole Puncher Unit-A1 Requires either Staple or Booklet Finisher-AC1. Punch Hole type: 4 holes (SWE) Paper Weight: 52-300 gsm Paper Size: A3, A4, A4R</p> |
| <p>Perfect Binder-F1</p> | <p>(Requires either the STAPLE FINISHER-AG1 or BOOKLET FINISHER-AG1) Booklet size: 203 x 138 mm to 297 x 216 mm Booklet thickness: Up to 25mm Cutting Range: Top/bottom: 6.5 to 39.5mm at each edge, fore edge: 6.5 to 49.5mm Body pages: Sizes: A4, SRA4, Free size (257 x 182 mm to 320 x 228.6 mm) Paper weight and number of sheets: Thin Paper (52-63 gsm): 30-200 sheets Plain Paper (64-80 gsm): 10-200 sheets Plain Paper (81-90 gsm): 10-150 sheets Thick Paper (91-105 gsm): 10-150 sheets Thick Paper (106-163 gsm): up to 10 sheets as insertion sheet or up to 25mm as thickness of bunch Cover: Number of Sheets: 1 sheet Sizes: A3, SRA3, Free size (257 x 364 mm to 330.2 x 487.7mm) Paper weight: 90 to 300 gsm Tray capacity: Approx.127mm or approx.1,000 sheets of paper as a total Dimensions : 922 mm x 791 mm x 1,300 mm Weight Approx. 308kg Power: 220-240V, 50/60Hz, 3.0A</p> | <p>Finisher Jogger Kit-A1</p> | <p>Basic information: Enables DFD connectivity directly beside the engine Paper Weight: Plain Paper 52-350 gsm, Coated Paper 128-350gsm Paper Size: 182 x 182 mm - 330.2 x 487.7 mm Optionals: Finisher Bridge Height Kit 1002-A1 (Standard DFD height is 860 mm) Dimensions (W x D x H): 300 mm x 745 mm x 1040 mm Weight: Approx. 60 kg Power: 90-264V, 47-63Hz, more than 10A</p> |
| <p>High Capacity Stacker-J1</p> | <p>Paper Size: A3, A4, A4R, A5R, SRA3, 13"x19", Free size (140 x 182 mm to 330.2 x 1,300 mm) Paper Weight: 52 to 350 gsm Output Capacity Stack tray: 6,000 sheets (80 gsm) in two stacks of 3,000 sheets each Top Tray: 200 sheets (80 gsm, 140 x 182 mm to 330.2 x 762mm), 100 sheets (210 x 762.1 mm to 330.2 x 1,300 mm) Dimensions (W x D x H): 899 mm x 745 mm x 1,040 mm Weight: Approx. 120 kg Power: 90-264V, 47-63Hz, 10A</p> | <p>Finisher Bridge-A1</p> | <p>Basic information: Offers connectivity of Staple Finisher-AG1 and Booklet Finisher-AG1 with 3rd party DFD finishing equipments. Always in combination with DFD Adapter-B1. Paper Weight: Plain Paper 52-350gsm, Coated Paper 128-350 gsm Paper Size: 182 x 182 mm - 330.2 x 487.7 mm Dimensions (W x D x H): 600 mm x 745 mm x 150 mm Weight: Approx. 30 kg Power: Power and control from DFD Adapter-A1</p> |
| <p>Staple Finisher-AC2 (only compatible with V800 and V700)</p> | <p>Lower Tray (A) Capacity: A4/ASR 3000 sheets (81 gsm), A4R/A3/SRA3/13"x19" 1500 sheets (81 gsm), Long sheet* (Over 487.7 mm up to 762 mm length) 100 sheets (79 gsm) Long sheet* (Over 762mm length) 1 sheet All size of thin paper (52-59 gsm) 1,500 sheets Capacity for coated paper is half of that for plain paper</p> | <p>3rd Party Finishers</p> | <p>Basic information: The imagePRESS V900 series can be configured also with 3rd party finishers. Please find here a list of listed and approved finishers. Plockmatic BLM35 Booklet Maker and Plockmatic BLM50 Upgrade Kit Plockmatic MPS (Multi-Purpose Stacker) GBC MF ProPuncher</p> |
| <p>Upper Tray (B) Capacity: A4/ASR 250 sheets (80 gsm), A4R/A3/SRA3/13"x19" 125 sheets (80 gsm) Mid Tray (C) Capacity: A4/ASR 250 sheets (80 gsm), A4R/A3/SRA3/13"x19" 125 sheets (80 gsm) Paper Weight for Tray A: Non Sort 52-350 gsm, Bunch Shift / Staple 52-256 gsm excluding duplex printed thin paper (52-59 gsm) and any special media, Eco Staple 52-105 gsm Paper Weight for Tray B/C: Non Sort / Bunch Shift 52-256 gsm excluding duplex printed thin paper (52-59 gsm), coated paper (85-105.9 gsm) and any special media Staple Position: Corner, Double Staple Capacity: <Non coated media, 52-90 gsm> A4: 65 sheets, A3/A4R: 40 sheets <Coated media> 2 sheets Dimensions (W x D x H): 527 mm (Max 656 mm*) x 623 mm x 1,099 mm (Max 1,195 mm*)</p> | <p>*Long Sheet Tray is required</p> <p>*when the auxiliary tray is extended.</p> <p>Weight: Approx. 36 kg</p> | <p>STAPLE CARTRIDGE</p> | <p>STAPLE-N1 - for Stapling (3 x 5,000 pcs) (for Staple Finisher-AG1 and Booklet Finisher-AG1) STAPLE-P1 - for Saddle Stitching (2 x 5,000 pcs) (for Booklet Finisher-AG1) STAPLE CARTRIDGE-X1 - For Stapling (3 x 5,000 pcs) (Staple Finisher-AC1 and Booklet Finisher-AC1) STAPLE CARTRIDGE-Y1 - For saddle stitching (2 x 2,000 pcs) (for Booklet Finisher-AC1)</p> |

Software & Solutions



Canon Ireland
 3006 Lake Drive
 Citywest, Saggart
 Co. Dublin, Ireland
 Telephone No: 01 2052400
 Facsimile No: 01 2052525
 canon.ie

Canon (UK) Ltd
 The Bower
 4 Roundwood Avenue
 Stockley Park
 Uxbridge
 UB11 1AF

Canon Inc.
 canon.com
Canon Europe
 canon-europe.com
 English edition
 © Canon Europa N.V., 2022